



36Ah Portable Lifepo4 Power Supply Station For Home Appliances

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: XWELL
- Certification: UN38.3, MSDS, UL, CB, BIS, PSE, GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE
- Model Number: XW-1000W-01
- Minimum Order Quantity: 1 pcs
- Packaging Details: Carton
- Delivery Time: 7-10 working days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 pcs per month



Product Specification

- Capacity: 36Ah (8SP)
- LCD Display: The Display Shows
- Over Temperature: ≥ 85
- Over Temperature Recovery: ≤ 70
- Charging Parameters: DC 12-24V / 5A
- Batteries Type: LiFePO4 Battery
- Input Power Supply: 12V-24V/1-5A
- AC Output: AC110V/220V/50Hz/60Hz
- USB Output: QC3.0 Fast Charging, 5V-3A, 9V-2A, 12V-1.5A, 18W Total Power
- Type-C Output: PD 120W Output
- Highlight: **Portable Lifepo4 Power Supply,
36Ah Lifepo4 Power Supply,
Home portable lifepo4 power station**

Product Description

Home Appliances Portable Lithium Battery Power Station Easy Expansion And Customization Dropshipping

Designed with durable exterior shell with convenient handle, the 5521 LiFePo4 battery ensures safety of power station. It is quite and free of emissions when charging, its you must-have power station for home and outdoors. 12 months product warranty, any questions about the product please contact us, we will provide our most professional service to you!

Features

1. Lithium batteries are capable of storing a significant amount of energy in a small space.
2. them to provide multiple charges to electronic devices without needing to be recharged themselves.
3. Many portable lithium batteries feature fast charging technology
4. them to charge electronic devices more quickly than traditional charging methods.

Specification

Category	Project	Specifications
INPUT	DC input	DC5521 12-24V-5A
	DC input	PD 120W
AC OUT 220V	AC output voltage	1 port, AC220V±5%
	AC output power	1000W
	AC output over power protection	1000W Approximately
	AC output waveform	pure sine wave
	AC output peak	1200W Peak maintenance time <50ms
	frequency	50Hz/60Hz
USB output port	USB1 output	QC3.0 MAX 18 W 12V / 1.5A ; SCP maximum output power: maximum 18W
	USB2 output	QC3.0 MAX 18 W 12V / 1.5A ; SCP maximum output power: maximum 100W
	TYPE-C1 output	PD / QC3.0 MAX 30W 12V/2.5A
DC12V output	DC1 DC2 output	12V / 10A MAX
TYPE-C output/input	TYPE-C2	PD 100W output
Batteries	type	LiFePO4 battery / 3600mAh
	capacity	36Ah (8SP)
	power	920Wh
	cycle life	1000+ times
Charging parameters		DC 12-24V / 5A
charging time	5 - 6H	Charge from 0% to 100% (automatic cut-off)
Full voltage	21.9V ±0.1V	The voltage when the battery is charged to the automatic cut-off
LCD display	Display power;charging, stop charging status	Battery percentage and battery column display
	DC, AC, inverter status	The display shows
boot static		<10W
Protective function		Short circuit, overload, over temperature, over voltage, over current, under voltage, etc.
over temperature protection	over temperature protection	≥85
	over temperature recovery	≤70

Our services

1. Your inquiry related to our products price will be replied in 24 hours.
2. Experienced staffs to answer all your enquiries in fluent English
3. We make the OEM and ODM service for more than 5 years
4. Protection of your sales area, ideas of design and all your private information.
5. No matter big order or small order, we will provide all the best quality, best service.
6. If our products have any problem that we caused, they will be sent free in the next order.

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou,
China