



# Customized Lifepo4 Solar Storage Lithium Battery 48V 51.2V 100Ah 200Ah

# **Basic Information**

Place of Origin: ChinaBrand Name: XWELL

 Certification: UN38.3,MSDS,UL,CB,BIS,PSE,GB4943.1 safety standard, CE, FCC, ROHS, battery

UN38.3, MSDS, UL, CB, BIS, PSE

Model Number: XW-10240W-1

Minimum Order Quantity: 1 pcsPackaging Details: Carton

Delivery Time: 7-10 working days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

Supply Ability: 5000 pcs per month



# **Product Specification**

Nominal Voltage: 48 51.2 Volts

Nominal Capacity: 50 100 200 Amper Hour
Nominal Energy: 2560 5120 10240 Wh
Cell Type: LiFePO4 Prismatic Cell

Discharge Current: 50AMax Charge Current: 50ADischarge Cut-off Voltage: 42.5V

• Display: LCD Optional

Communication Interface: RS485, RS232, CANCycle Life: >6000 Cycles(80%DOD)

Highlight: Customized Solar Storage Lithium Battery,

Solar Storage Lithium Battery 48V, 100Ah solar lithium storage battery

# **Product Description**

#### Lifepo4 Batteries Solar Storage 48V 51.2V 100Ah 200Ah Rackmount Lithium Ion Iron Phosphate Battery

#### How do I choose the correct lithium deep cycle battery for my application?

In most standard 12, 24, or 48 volt systems, the best choice of lithium battery is LiFePO4 (Lithium Iron Phosphate/Pouch/Primary battery cell). The voltage of this type of battery is very similar to an AGM and will work great with readily available system components for your RV, boat, off-grid power system, solar house(TV, refrigerator, washing machine, air conditioner, water heater, microwave oven, induction cooker, dishwasher, printer, computer), Telecommunication Tower, hybrid & off-grid solar energy system applications.


#### **Rackmount Lithium Battery Features**

- 1. Military Grade Cells
- 2. Dedicate Production
- 3. Customized OEM and ODM Service
- 4. Intelligent BMS

#### **Rackmount Lithium Battery Specification**


Model	51.2V50Ah	51.2V100Ah	51.2V200Ah		
Nominal voltage		51.2V			
Nominal capacity (kwh)	2.56	5.12	10.24		
Cell type	LiFePO4				
Standard charge voltage	54.6V(adjustable)				
Max charge current	50A				
Discharge cut-off voltage	42.5V(adjustable)				
Max discharge current	50A				
Display	LCD(Optional)				
Communication interface	CAN/RS485/RS232				
Cycle life	>6000 Cycles (80%DOD)				
Charge temperature range	0~45°C				
Discharge temperature range	-20~60°C				
Color	Black				
Dimension (mm)	442x410x133 3U	442x410x177 4U	550x442x220 5U		
Weight	About 35Kg	About 42Kg	About 84Kg		
Installation method	Rack Mount				

#### Cell Specification of Rackmount Lithium Battery




#	Item	Parameter
A	Height	119±1.0 mm
В	Width	160±1.0 mm
С	Thickness	≤50 mm
D	Tabs Distance	97±0.5 mm

# **Operation Pannel of Rackmount Lithium Battery**




#	Item	Function	#	Item	Function
(1)	Case Hanger	mount in 19 inch cabinet or anti-seismic rake	(8)	SOC Indicator	indicate battery capacity percentage
(2)	Handle	easy to handle, move and install	(9)	Dry Contact	remote on/off control by signal wires
(3)	Reset Switch	restart and wake up the battery	(10)	Comm. Port	RS485+RS232
(4)	On/Off Indicator	turn on/off green and indicate battery on/off	(11)	Comm. Port	RS232
(5)	Working Indicator	turn on green and indicate normal operation	(12)	Comm. Port	RS485+RS232
(6)	Alarm Indicator	turn on red when there is alarm or failure	(13)	Terminal Bar	charge and discharge terminal
(7)	DIP Switch	define battery IP for parallel connection	(14)	DC Switch	turn battery on/off

# Size of Rackmount Lithium Battery



### **Structure of Rackmount Lithium Battery**



#	Item	Material
(1)	Case Cover	SPCC
(2)	Case Hanger	SPCC
(3)	Insulation Sheet	Ethoxyline
(4)	Bus-Bar	Aluminum Alloy
(5)	Battery Cell	LFP, Aluminum Shel
(6)	Module Side Plate	ABS / PC
(7)	Cell Binding Loop	Plastic Steel
(8)	Case Bottom	SPCC
(9)	Insulating Wiring Terminal	Bakelite
(10)	Side Plate Combination Board	SPCC
(11)	BMS	PCB
(12)	Commination Board	PCB
(13)	DC Switch	1
(14)	Handle	Sherardized SPCC
(15)	Case Front Cover	SPCC
(16)	Terminal Bar (+ & -)	1

# **Application of Rackmount Lithium Battery**

# **Application Scenario**



**Data Center** 



C&I Park



**Telecom Base** 



**Medical Equipment** 

#### Why choose us?

We production of battery products are widely used in communications, power, financial systems, uninterruptible power supply systems (UPS), power plant and substation switch control, solar panels, controllers inverter etc solar systems, emergency lighting, alarm systems, cars, ships, motorcycles, electric bicycles and other industries. Sales network covers all provinces, municipalities, autonomous regions and established offices in various places and after-sales service center. Our team with Yuasa ,BYD battery senior consultant,High quality technical management team, advanced production and testing equipment to ensure the quality of the battery is reliable.



# XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.



+86 18620492985



sales@esslithiumbattery.com



esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou,